

---

# **edX Django REST Framework Extensions Documentation**

***Release 6.6.0***

**edX**

**Jul 13, 2021**



---

## Contents

---

<b>1 Requirements</b>	<b>3</b>
<b>2 Installation</b>	<b>5</b>
<b>3 Table of Contents</b>	<b>7</b>
3.1 Settings . . . . .	7
3.2 Authentication . . . . .	8
3.3 Middleware . . . . .	8
3.4 Permissions . . . . .	9
3.5 Utility Functions . . . . .	10
3.6 Change Log . . . . .	10
<b>Python Module Index</b>	<b>13</b>
<b>Index</b>	<b>15</b>



This package provides extensions for [Django REST Framework](#) that are useful for developing on the edX platform.



# CHAPTER 1

---

## Requirements

---

- Python (2.7, 3.5, 3.6)
- Django (1.8, 1.9, 1.10, 1.11)
- Django REST Framework (3.2+)



# CHAPTER 2

---

## Installation

---

Install using pip:

```
$ pip install edx-drf-extensions
```



# CHAPTER 3

---

## Table of Contents

---

### 3.1 Settings

All settings for this package reside in a dict, `EDX_DRF_EXTENSIONS`. Within this dict, the following keys should be specified, depending on the functionality you are using.

#### 3.1.1 BearerAuthentication

These settings are used by the `BearerAuthentication` class.

##### `OAUTH2_USER_INFO_URL`

Default: None

URL of an endpoint on the OAuth2 provider where `BearerAuthentication` can retrieve details about the user associated with the provided access token. This endpoint should return a JSON object with user details and HTTP 200 if, and only if, the access token is valid. See `BearerAuthentication.process_user_info_response()` for an example of the expected data format.

#### 3.1.2 JwtAuthentication

These settings are used by the `JwtAuthentication` class. Since this class is based on `JSONWebTokenAuthentication`, most of its settings can be found in the documentation for `rest_framework_jwt` at <http://getblimp.github.io/django-rest-framework-jwt/#additional-settings>.

##### `JWT_AUTH['JWT_VERIFY_AUDIENCE']`

Default: True

If you do *not* want to verify the JWT audience, set the 'JWT\_VERIFY\_AUDIENCE' key in the `JWT_AUTH` setting to `False`.

#### `JWT_PAYLOAD_USER_ATTRIBUTES`

Default: `('email',)`

The list of user attributes in the JWT payload that `JwtAuthentication` will use to update the local `User` model. These payload attributes should exactly match the names the attributes on the local `User` model.

## 3.2 Authentication

Authentication classes are used to associate a request with a user. Unless otherwise noted, all of the classes below adhere to the Django REST Framework's API for authentication classes.

## 3.3 Middleware

This module contains middleware to ensure best practices of DRF and other endpoints..

`class RequestCustomAttributesMiddleware(get_response=None)`

Adds various request related custom attributes.

**Possible custom attributes include:**

`request_authenticated_user_set_in_middleware`: Example values: 'process\_request', 'process\_view', 'process\_response', or 'process\_exception'. Attribute won't exist if user is not authenticated.

`request_auth_type_guess`: Example values include: **no-user, unauthenticated, jwt, bearer, other-token-type, jwt-cookie, or session-or-other**. Note: These are just guesses because if a token was expired, for example,

the user could have been authenticated by some other means.

`request_client_name`: The client name from `edx-rest-api-client` calls. `request_referer` `request_user_agent`: The user agent string from the request header. `request_user_id`: The user id of the request user. `request_is_staff_or_superuser`: *staff* or *superuser* depending on whether the

user in the request is a django staff or superuser.

This middleware is dependent on the `RequestCacheMiddleware`. You must include this middleware later. For example:

```
MIDDLEWARE = (
    'edx_django_utils.cache.middleware.RequestCacheMiddleware',
    'edx_rest_framework_extensions.middleware.RequestCustomAttributesMiddleware',
)
```

This middleware should also appear after any authentication middleware.

`process_exception(request, exception)`

Django middleware handler to process an exception

`process_request(request)`

Caches if authenticated user was found.

```
process_response (request, response)
    Add custom attributes for various details of the request.

process_view (request, view_func, view_args, view_kwargs)
    Caches if authenticated user was found.

class RequestMetricsMiddleware (*args, **kwargs)
    Deprecated class for handling middleware. Class has been renamed to RequestCustomAttributesMiddleware.
```

## 3.4 Permissions

Permissions determine whether a request should be granted or denied access. Unless otherwise noted, all of the classes below adhere to the Django REST Framework’s API for permission classes.

```
class IsStaff
    Allows access to “global” staff users..

    has_permission (request, view)
        Return True if permission is granted, False otherwise.

class IsSuperuser
    Allows access only to superusers.

    has_permission (request, view)
        Return True if permission is granted, False otherwise.

class IsUserInUrl
    Allows access if the requesting user matches the user in the URL.

    has_permission (request, view)
        Return True if permission is granted, False otherwise.

class JwtHasContentOrgFilterForRequestedCourse
    The JWT used to authenticate contains the appropriate content provider filter for the requested course resource.

    has_permission (request, view)
        Ensure that the course_id kwarg provided to the view contains one of the organizations specified in the content provider filters in the JWT used to authenticate.

class JwtHasScope
    The request is authenticated as a user and the token used has the right scope.

    has_permission (request, view)
        Return True if permission is granted, False otherwise.

class JwtHasUserFilterForRequestedUser
    The JWT used to authenticate contains the appropriate user filter for the requested user resource.

    has_permission (request, view)
        If the JWT has a user filter, verify that the filtered user value matches the user in the URL.

class JwtRestrictedApplication
    Allows access if the request was successfully authenticated with JwtAuthentication by a RestrictedApplication.

    has_permission (request, view)
        Return True if permission is granted, False otherwise.

class LoginRedirectIfUnauthenticated
    A DRF permission class that will login redirect unauthorized users.
```

It can be used to convert a plain Django view that was using `@login_required` into a DRF APIView, which is useful to enable our DRF JwtAuthentication class.

Requires `JwtRedirectToLoginIfUnauthenticatedMiddleware` to work.

**class NotJwtRestrictedApplication**

Allows access if either the request was not authenticated with JwtAuthentication, or if it was successfully authenticated with JwtAuthentication and the Jwt was not flagged as restricted.

Note: Anonymous access will also pass this permission.

**has\_permission(*request, view*)**

Return *True* if permission is granted, *False* otherwise.

## 3.5 Utility Functions

This module contains useful utility functions.

## 3.6 Change Log

### 3.6.1 Unreleased

#### 3.6.2 [6.6.0] - 2021-07-13

##### Added

- Added support for django3.1 and 3.2

#### 3.6.3 [6.5.0] - 2021-02-12

##### Added

- Added a new custom attribute `jwt_auth_failed` to both monitor failures, and to help prepare for future refactors.

#### 3.6.4 [6.4.0] - 2021-01-19

##### Added

- Added a new custom attribute `request_is_staff_or_superuser`

#### 3.6.5 [6.3.0] - 2021-01-12

##### Removed

- Drop support for Python 3.5

## 3.6.6 [6.2.0] - 2020-08-24

### Updated

- Renamed “custom metric” to “custom attribute” throughout the repo. This was based on a [decision \(ADR\)](#) captured in `edx-django-utils`.
  - Deprecated `RequestMetricsMiddleware` due to rename. Use `RequestCustomAttributesMiddleware` instead.

## 3.6.7 [6.1.2] - 2020-07-19

### Fixed

- `_get_user_from_jwt` no longer throws an *UnsupportedMediaType* error for failing to parse “new user” requests.

## 3.6.8 [6.1.1] - 2020-07-19

### Fixed

- Latest `drf-jwt` is throwing error in case of any other Authorization Header. Fixing that issue in `JwtAuthentication` class.

## 3.6.9 [6.1.0] - 2020-06-26

### Changed

- Update `drf-jwt` to pull in new allow-list(they called it blacklist) feature.

### Added

### Fixed

## 3.6.10 [6.0.0] - 2020-05-05

### Changed

- BREAKING CHANGE:** Renamed ‘request\_auth\_type’ to ‘request\_auth\_type\_guess’. This makes it more clear that this metric could report the wrong value in certain cases. This could break dashboards or alerts that relied on this metric.
- BREAKING CHANGE:** Renamed value `session-or-unknown` to `session-or-other`. This name makes it more clear that it is the method of authentication that is in question, not whether or not the user is authenticated. This could break dashboards or alerts that relied on this metric.

### Added

- Added ‘jwt-cookie’ as new value for ‘request\_auth\_type\_guess’.

- Added new ‘request\_authenticated\_user\_found\_in\_middleware’ metric. Helps identify for what middleware step the request user was set, if it was set. Example values: ‘process\_request’, ‘process\_view’, ‘process\_response’, or ‘process\_exception’.

## Fixed

- Fixed/Added setting of authentication metrics for exceptions as well.
- Fixed ‘request\_auth\_type\_guess’ to be more accurate when recording values of ‘unauthenticated’ and ‘no-user’.

---

## Python Module Index

---

### e

`edx_rest_framework_extensions.middleware`,  
    8  
`edx_rest_framework_extensions.permissions`,  
    9  
`edx_rest_framework_extensions.utils`, 10



## Index

<b>E</b>		
edx_rest_framework_extensions.middleware (module), 8	JwtHasUserFilterForRequestedUser (class in edx_rest_framework_extensions.permissions), 9	
edx_rest_framework_extensions.permissions (module), 9	JwtRestrictedApplication (class in edx_rest_framework_extensions.permissions), 9	
edx_rest_framework_extensions.utils (module), 10		
<b>H</b>		
has_permission () (IsStaff method), 9		
has_permission () (IsSuperuser method), 9		
has_permission () (IsUserInUrl method), 9		
has_permission () (JwtHasContentOrgFilterForRe- questedCourse method), 9		
has_permission () (JwtHasScope method), 9		
has_permission () (JwtHasUserFilterForRequeste- dUser method), 9		
has_permission () (JwtRestrictedApplication method), 9		
has_permission () (NotJwtRestrictedApplication method), 10		
<b>I</b>		
IsStaff (class in edx_rest_framework_extensions.permissions), 9		
IsSuperuser (class in edx_rest_framework_extensions.permissions), 9		
IsUserInUrl (class in edx_rest_framework_extensions.permissions), 9		
<b>J</b>		
JwtHasContentOrgFilterForRequestedCourse (class in edx_rest_framework_extensions.permissions), 9		
JwtHasScope (class in edx_rest_framework_extensions.permissions), 9		
<b>L</b>		
LoginRedirectIfUnauthenticated (class in edx_rest_framework_extensions.permissions), 9		
<b>N</b>		
NotJwtRestrictedApplication (class in edx_rest_framework_extensions.permissions), 10		
<b>P</b>		
process_exception () (RequestCustomAttributesMid- dleware method), 8		
process_request () (RequestCustomAttributesMid- dleware method), 8		
process_response () (RequestCustomAttributesMid- dleware method), 8		
process_view () (RequestCustomAttributesMid- dleware method), 9		
<b>R</b>		
RequestCustomAttributesMiddleware (class in edx_rest_framework_extensions.middleware), 8		
RequestMetricsMiddleware (class in edx_rest_framework_extensions.middleware), 9		