
edX Django REST Framework Extensions Documentation

Release 1.2.3

edX

February 23, 2018

1	Requirements	3
2	Installation	5
3	Table of Contents	7
3.1	Settings	7
3.2	Authentication	8
3.3	Permissions	9
3.4	Utility Functions	9
	Python Module Index	11

This package provides extensions for [Django REST Framework](#) that are useful for developing on the edX platform.

Requirements

- Python (2.7, 3.5, 3.6)
- Django (1.8, 1.9, 1.10, 1.11)
- Django REST Framework (3.2+)

Installation

Install using pip:

```
$ pip install edx-drf-extensions
```

Table of Contents

Settings

All settings for this package reside in a dict, *EDX_DRF_EXTENSIONS*. Within this dict, the following keys should be specified, depending on the functionality you are using.

BearerAuthentication

These settings are used by the *BearerAuthentication* class.

`OAuth2_USER_INFO_URL`

Default: None

URL of an endpoint on the OAuth2 provider where *BearerAuthentication* can retrieve details about the user associated with the provided access token. This endpoint should return a JSON object with user details and HTTP 200 if, and only if, the access token is valid. See *BearerAuthentication.process_user_info_response()* for an example of the expected data format.

JwtAuthentication

These settings are used by the *JwtAuthentication* class. Since this class is based on *JSONWebTokenAuthentication*, most of its settings can be found in the documentation for *rest_framework_jwt* at <http://getblimp.github.io/django-rest-framework-jwt/#additional-settings>.

`JWT_AUTH['JWT_VERIFY_AUDIENCE']`

Default: True

If you do *not* want to verify the JWT audience, set the '`JWT_VERIFY_AUDIENCE`' key in the `JWT_AUTH` setting to `False`.

`JWT_PAYLOAD_USER_ATTRIBUTES`

Default: ('email',)

The list of user attributes in the JWT payload that *JwtAuthentication* will use to update the local `User` model. These payload attributes should exactly match the names the attributes on the local `User` model.

Authentication

Authentication classes are used to associate a request with a user. Unless otherwise noted, all of the classes below adhere to the Django [REST Framework's API for authentication classes](#).

class `BearerAuthentication`

Simple token based authentication.

This authentication class is useful for authenticating an OAuth2 access token against a remote authentication provider. Clients should authenticate by passing the token key in the “Authorization” HTTP header, prepended with the string “*Bearer* “.

This class relies on the `OAUTH2_USER_INFO_URL` being set to the value of an endpoint on the OAuth provider, that returns a JSON object with information about the user. See `process_user_info_response` for the expected format of this object. This data will be used to get, or create, a `User`. Additionally, it is assumed that a successful response from this endpoint (authenticated with the provided access token) implies the access token is valid.

Example Header: Authorization: Bearer 401f7ac837da42b97f613d789819ff93537bee6a

`authenticate_credentials` (*token*)

Validate the bearer token against the OAuth provider.

Parameters `token` (*str*) – Access token to validate

Returns

tuple containing:

user (`User`): User associated with the access token
access_token (*str*): Access token

Return type (tuple)

Raises `AuthenticationFailed` – The user is inactive, or retrieval of user info failed.

`get_user_info` (*token*)

Retrieves the user info from the OAuth provider.

Parameters `token` (*str*) – OAuth2 access token.

Returns dict

Raises `UserInfoRetrievalFailed` – Retrieval of user info from the remote server failed.

`get_user_info_url` ()

Returns the URL, hosted by the OAuth2 provider, from which user information can be pulled.

`process_user_info_response` (*response*)

Process the user info response data.

By default, this simply maps the edX user info key-values (example below) to Django-friendly names. If your provider returns different fields, you should sub-class this class and override this method.

```
{
    "username": "jdoe",
    "email": "jdoe@example.com",
    "first_name": "Jane",
    "last_name": "Doe"
}
```

Parameters `response` (*dict*) – User info data

Returns dict

class JwtAuthentication

JSON Web Token based authentication.

This authentication class is useful for authenticating a JWT using a secret key. Clients should authenticate by passing the token key in the “Authorization” HTTP header, prepended with the string “JWT “.

This class relies on the `JWT_AUTH` being configured for the application as well as `JWT_PAYLOAD_USER_ATTRIBUTES` being configured in the `EDX_DRF_EXTENSIONS` config.

At a minimum, the JWT payload must contain a username. If an email address is provided in the payload, it will be used to update the retrieved user’s email address associated with that username.

Example Header: Authorization: JWT eyJhbGciOiJSUzUxMiIsInR5cCI6IkpXVCJ9.eyJzdWIiOiJmYzJiNzIwMTE0YmIwN2I0ImFkbWluaXN0cmF0b3IiOmZhbHNiLCJuYXW1IjoiaG9ub3IiLCJleHA.QHDXdo8gDJ5p9uOErTLZtl2HK_61kgLs71VHpJUZpIYMKEd38uf1vj-4HZkzeNBnZZZ3Kdvq7F8ZioREPKNyEVSm2mnz11v49EthehN9kwfUgFgPXfUh-pCvLDqwCCTdAXMcTJ8qufzEPTYYY54IY

authenticate_credentials (*payload*)

Get or create an active user with the username contained in the payload.

get_jwt_claim_attribute_map ()

Returns a mapping of JWT claims to user model attributes.

Returns dict

Permissions

Permissions determine whether a request should be granted or denied access. Unless otherwise noted, all of the classes below adhere to the Django [REST Framework’s API for permission classes](#).

class IsSuperuser

Allows access only to superusers.

Utility Functions

This module contains useful utility functions.

jwt_decode_handler (*token*)

Decodes a JSON Web Token (JWT).

Notes

- Requires “exp” and “iat” claims to be present in the token’s payload.
- Supports multiple issuer decoding via settings.`JWT_AUTH['JWT_ISSUERS']` (see below)
- Aids debugging by logging `DecodeError` and `InvalidTokenError` log entries when decoding fails.

Examples

Use with `django-rest-framework-jwt`, by changing your Django settings:

```
JWT_AUTH = {
    'JWT_DECODE_HANDLER': 'edx_rest_framework_extensions.utils.jwt_decode_handler',
    'JWT_ISSUER': 'https://the.jwt.issuer',
    'JWT_SECRET_KEY': 'the-jwt-secret-key', (defaults to settings.SECRET_KEY)
    'JWT_AUDIENCE': 'the-jwt-audience',
}
```

Enable multi-issuer support by specifying a list of dictionaries as `settings.JWT_AUTH['JWT_ISSUERS']`:

```
JWT_ISSUERS = [
    {
        'ISSUER': 'test-issuer-1',
        'SECRET_KEY': 'test-secret-key-1',
        'AUDIENCE': 'test-audience-1',
    },
    {
        'ISSUER': 'test-issuer-2',
        'SECRET_KEY': 'test-secret-key-2',
        'AUDIENCE': 'test-audience-2',
    }
]
```

Parameters `token` (*str*) – JWT to be decoded.

Returns Decoded JWT payload.

Return type dict

Raises

- `MissingRequiredClaimError` – Either the `exp` or `iat` claims is missing from the JWT payload.
- `InvalidTokenError` – Decoding fails.

e

`edx_rest_framework_extensions.authentication,`
 [8](#)
`edx_rest_framework_extensions.permissions,`
 [9](#)
`edx_rest_framework_extensions.utils,` [9](#)

A

`authenticate_credentials()` (BearerAuthentication method), 8
`authenticate_credentials()` (JwtAuthentication method), 9

B

`BearerAuthentication` (class in `edx_rest_framework_extensions.authentication`), 8

E

`edx_rest_framework_extensions.authentication` (module), 8
`edx_rest_framework_extensions.permissions` (module), 9
`edx_rest_framework_extensions.utils` (module), 9

G

`get_jwt_claim_attribute_map()` (JwtAuthentication method), 9
`get_user_info()` (BearerAuthentication method), 8
`get_user_info_url()` (BearerAuthentication method), 8

I

`IsSuperuser` (class in `edx_rest_framework_extensions.permissions`), 9

J

`jwt_decode_handler()` (in module `edx_rest_framework_extensions.utils`), 9
`JwtAuthentication` (class in `edx_rest_framework_extensions.authentication`), 9

P

`process_user_info_response()` (BearerAuthentication method), 8